
APPENDIX 2

DISPATCH CONDITION EXAMPLES

Listed below is a random selection of Dispatch Condition Ratings which can be issued through PressureMAP. Examples of the normal aging of a dispatch are shown below. However, in some cases a dispatch may appear to age more quickly, so it is advisable to check the date indicated in the Task Number against the apparent “age” of a dispatch.

<u>Dispatch Conditions</u>	<u>Rating Code</u>
Manifold/meter panel flow gained 7.0 SCFH in 24 hr (if range for the device is between 47.5 and 95.0 SCFH)	****
Source/end pipe PTD lost 2.0 PSI in 24 hr	****
UG Cable PTD lost 3.0 PSI in 24 hr	****
UG Cable PTD lost 3.0 PSI in 24 hr (second consecutive day uncleared)	-***
UG Cable PTD lost 3.0 PSI in 24 hr (third consecutive day uncleared)	--**
UG Cable PTD lost 3.0 PSI in 24 hr (fourth consecutive day uncleared)	---*
Manifold/meter panel flow gained 4.0 SCFH in 24 hr (Sharp sign rating indicates that more than one dispatch condition was found at this location.)	###
Source/end pipe PTD lost 1.0 PSI in 48 hr	***
Manifold/meter panel flow gained 3.0 SCFH in 48 hr (if range for the device is less than 47.5 SCFH)	***
Manifold/meter panel flow gained 3.0 SCFH in 48 hr (second consecutive day uncleared)	-**
Manifold/meter panel flow gained 3.0 SCFH in 48 hr (third consecutive day uncleared)	--*
Manifold/meter panel flow gained 3.0 SCFH in 48 hr (fourth consecutive day uncleared)	--*

OPERATIONS

Dispatch Conditions

Rating Code

Manifold/meter panel lost 2.0 SCFH to 0, turned off?	**
Buried Cable PTD lost 4.0 PSI in 72 hrs	**
Source/end pipe PTD at 5.0 PSI	*
UG PTD at 2.0 PSI with pipe at 7.0 PSI	*
Manifold or meter flow at more than 300% of OAU	R
Aerial PTD at 2.0 PSI with pipe at 5.0 PSI	R